



Brock's Performance • 4064 E. Patterson Road • Dayton, OH 45430 • Phone: 937-912-0054 • Fax: 937-912-0062

NOISE SUPPRESSORS (2.00" & 2.25") PRODUCT INFORMATION

Noise Suppressors (903574, 903587, 903600 and 903626) are designed to provide users with an easily removable option for significant noise reduction with minimal effect on horsepower and sound quality.

Package Contents:

Noise Suppressor shown:

1. One (1) Noise Suppressor Insert
2. One (1) Noise Suppressor Mounting Body
3. Two (2) Mounting Clamps
4. Two (2) Button Head Screws
5. Two (2) 5/16" Hex Nuts



Installation Notes:

Caution: Exhaust components will be HOT after use. Allow time to cool before installation or removal.

- Installs to 2.00" or 2.25" select Brocks Performance full exhaust systems and slip-ons.
- Easily installs using a 5/16" (8mm) wrench.
- The noise suppressor will sit flush with the muffler outlet. Use a soft-faced mallet to tap into place as needed (Fig 1).
- After installing the noise suppressor, give it a good pull to check for a secure fit to the muffler.
- The button head screws come installed with high-temp red threadlocker. The button head screws should not be removed during normal operation. In the event removal is required, apply high-temp red threadlocker to the upper four threads of the button head screws.
- The actual decibel reading from the exhaust will vary depending on the bike and modifications.
- **Note:** Due to heat, pressure, and vibration (**notably on the Ninja H2**) noise suppressor mounting nuts can loosen over time. Periodically check the noise suppressor for a secure fit.



All Brock's Performance products are designed for closed-course racetrack use ONLY!

For more information on Brock's Performance Warranty and Terms and Conditions: www.BrocksPerformance.com
> About Us > Terms and Conditions

For Questions and Comments: www.BrocksPerformance.com > Customer Service > Contact Us
or call the Tech Line 937-912-0054